



# Dehumidifier DRY-1500 STD and /S

Industrial dehumidifier

## Description

Industrial dehumidifier **DRY-1500**, available with canalizations or fixed installation, suitable for medium and large sized areas and able to deal with a large air amount. It is available in standard version or hot gas defrosting version (for unheated rooms). It is equipped with state-of-the-art compressors able to offer the best performance in every environmental conditions. Removable panels to facilitate inspections and maintenance. The structure is entirely made of coated and galvanized steel in order to guarantee durability and long-lasting excellent performances. Industrial unit which is extremely versatile in its use and installation, thanks to the vertical expulsion of the process air and to the possibility to be canalized if needed. The **DRY-1500** can be installed on a wheeled trolley to ease movements. Power source V/Ph/Hz 230/1/50. It is equipped with a washable air filter, **eco cooling gas R410A**, and is particularly suitable for commercial and industrial use. A test is conducted on every unit before the delivery.

## Versioni

Industrial dehumidifier available in **DRY-1500 STD** version (working range: +10/+36°C) and **DRY-1500/S** version with hot gas defrosting (working range: +1/+36°C).

## Fields of applicaion

This dehumidifier is suitable for: storehouses, industrial environment, cheese factories and meat aging rooms, food industries, swimming pools and gyms, hotels, hygroscopic material warehouses, archives, rental, auto workshops, cellars and basement rooms, etc.



 con gas 100%  
ecologico **R410A**

- Eco cooling gas R410A
- Digital electronic dumidostat
- High precision humidity probe
- Display temperature and humidity
- Unit vertical development
- Vertical air expulsion

DRY-1500 available in two versions:  
**DRY-1500 STD** and **DRY-1500/S**

## Features

- Eco cooling gas R410A
- ERP2015 fans
- FOOT PRINT plug
- Carter resistance compressor
- Unit vertical development
- Humidity temperature visualisation
- Galvanized steel structure
- High precision humidity probe


## Accessories

- /S version (hot gas defrosting)
- Remote mechanical hygrostat
- Wheeled trolley
- Air filter with frame for canalization
- High precision digital hygrostat
- Air expulsion camber
- Remote electronic hygrostat

## Technical data

Cooling gas	R410A
Dehumidification capacity (at 35°C and 80% of r.h.)	138,2 l/24h
Maximum power absorbed	2,8 kW
Maximum electricity absorbed	15,1 A
Total air flow rate	1200 m3/h
Maximum static pressure of the fan flow	50 Pa
Compressor	n. 1
Sound pressure level (free field at 1 mt)	59 db(A)
Dimensions (length x width x height)	101 x 62 x 50 cm
STD version working range	+10/+36 °C
/S version working range	+1/+36 °C
Humidity working range	45-99% u.r.
Weight	77 Kg
Air temperature increase (room temperature 20°C-60% R.H.)	+7,2 °C
Room heat load (room temperature 20°C-60% R.H.)	3,1

## Types of installations



Canalized installation


Free blowing expulsion

Installation on trolley

Floor installation

# Performance

Temp.	50% u.r.	60% u.r.	70% u.r.	80% u.r.
	dehumidification lt/24h			
10°C	15,6	22,0	28,6	37,2
15°C	22,0	32,7	42,8	53,7
20°C	31,9	44,7	59,2	74,0
25°C	45,1	61,6	77,0	93,9
30°C	57,4	77,8	96,8	117,8
35°C	67,5	91,2	109,4	138,2



# Dimensional

